



GEARED HEAD HEAVY DUTY LATHE MACHINE MODEL - VGH-267



E-mail: vinit@balajilathe.com • Web: www.balajilathe.com







MODEL - VGH-267 GEARED HEAD HEAVY DUTY LATHE MACHINE: TECHNICAL SPECIFICATIONS

BED								
LENGTH OF BED	7' (2100 mm)	9' (2740 mm)	10' (3040 mm)	12' (3650 mm)	14' (4260 mm)	16' (4850 mm)	18' (5450	20' (6050 mm)
ADMIT BETWEEN CENTRE	1000 mm	1600 mm	1900 mm	2500 mm	3100 mm	3700 mm	mm)	4900 mm

TYPE OF BED	Hardened Bed Ways		
HEIGHT OF CENTRE	267 mm (10-1/2")	304 mm (12")	
SWING OVER BED	525 mm	600 mm	
SWING OVER CROSS SLIDE	320 mm	395 mm	
SWING IN GAP	800 mm	875 mm	
WIDTH OF BED 325 mm		mm	
LENGTH OF GAP IN FRONT OF FACE PLATE	200 mm		

MAIN SPINDLE			
NO. OF SPINDLE SPEED	1.	2	
SPINDLE SPEED RANGE	30 to 1060 RPM *		
TAPER IN SPINDLE	MT-6		
SPINDLE BORE	50 mm	79 mm	104 mm
SPINDLE NOSE	A2-6	A2-8	A2-8

THREADS			
LEAD SCREW DIAMETER / PITCH	38 mm / 4 TPI		
NOS. OF THREADS/RANGE	METRIC: 24 / 0.5 mm to 15 mm PITCH		
(WITHOUT NORTON GEAR BOX)	INCH: 44 / 2 to 60 TPI		
NO. OF FEEDS	40		
RANGE OF LONGITUDINAL FEEDS	0.066 - 2 mm		
RANGE OF TRANSVERSE FEEDS	0.0165 - 0.5 mm		

TAIL STOCK	
TAIL STOCK SPINDLE DIAMETER	60.3 mm
TAPER IN TAIL STOCK QUILL	MT - 4
TRAVEL AND TOOLS	
CROSS SLIDE TRAVEL	280 mm
COMPOUND SLIDE TRAVEL	145 mm
TAIL STOCK SLEEVE TRAVEL	170 mm

TOOL POST SQUARE

SUITABLE ELECTRICAL HP

TOOL SHANK SIZE

- CHUCK BACK PLATE
- CENTREADAPTER
- DEAD CENTRES 2 NOS
- TOOL POST SPANNER
- MOTOR PULLEY
- THREAD DIAL INDICATOR
- CHANGE GEAR SET
- CHIPTRAY
- NORTON GEAR BOX WITH DOUBLE SHAFT

OPTIONAL ACCESSORIES:

- INDEPENDENT CHUCK
- SELF CENTRING CHUCK
- CHUCK BACK PLATE EXTRA
- STEADY REST
- FOLLOWREST
- FACE PLATE
- CARRIER PLATE
- TAPER TURNING ATTACHMENT
- COOLANT PUMP WITH TANK AND FITTINGS
- REAR TOOL POST
- ELECTRICALS (MOTOR, WIRING, SWITCH, V-BELTSAND FITTINGS)
- PANELBOARD
- SPLASH GUARD
- FOUNDATION ROUND PLATE WITH LEVELLING BOLTS
- QUICK CHANGE TOOL POST
- KEY WAY ATTACHMENT
- PADELSTOP
- ELECTRICAL THIRD SHAFT

NOTE: As improvements are constantly made in our machines, the above illustrations, specifications, dimensions and technical data are subject to modifications and change without prior notice and not binding on us.



120 mm

25 mm

3 HP / 5 HP (3 phase)*

Balaji Industrial Zone - A, Ribda Ardoi Road, Off National Highway, Ribda, Rajkot - 360 311. India. E-mail: vinit@balajilathe.com • Web: www.balajilathe.com • Cell: +91 94273 96228, 72260 41935.