



GEARED HEAD EXTRA HEAVY DUTY LATHE MACHINE VGH-558







VINIT MACHINES PVT. LTD.

E-mail: vinit@balajilathe.com • Web: www.balajilathe.com







MODEL - VGH-558 GEARED HEAD EXTRA HEAVY DUTY LATHE MACHINE: TECHNICAL SPECIFICATIONS

| BED | | | | | | | | | |
|----------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| LENGTH OF BED | 10' (3040 mm) | 12' (3650 mm) | 14' (4260 mm) | 16' (4850 mm) | 18' (5450 mm) | 20' (6050 mm) | 22' (6650 mm) | 24' (7250 mm) | 26' (7850 mm) |
| ADMIT BETWEEN CENTRE | 1200 mm | 1800 mm | 2400 mm | 3000 mm | 3600 mm | 4200 mm | 4800 mm | 5400 mm | 6000 mm |

| TYPE OF BED | Hardened Bed Ways | | |
|--------------------------------------|-------------------|-----------|--|
| HEIGHT OF CENTRE | 558 mm (22") | 609 (24") | |
| SWING OVER BED | 1075 mm | 1175 mm | |
| SWING OVER CROSS SLIDE | 750 mm | 850 mm | |
| SWING IN GAP | 1400 mm | 1500 mm | |
| WIDTH OF BED | 660 mm | | |
| LENGTH OF GAP IN FRONT OF FACE PLATE | 250 mm* | | |

| MAIN SPINDLE | | |
|----------------------|----------------|--|
| NO. OF SPINDLE SPEED | 8 | |
| SPINDLE SPEED RANGE | 14 to 200 RPM* | |
| TAPER IN SPINDLE | MT-6 | |
| SPINDLE BORE | 115 mm | |
| SPINDLE NOSE | A2-11 | |

| THREADS | | | |
|-----------------------------|----------------------------------|--|--|
| LEAD SCREW DIAMETER / PITCH | 44.4 mm / 2 TPI | | |
| NOS. OF THREADS/RANGE | METRIC: 24/0.5 mm to 15 mm PITCH | | |
| (FOR FULL NORTON GEAR BOX) | INCH: 44 / 2 to 60 TPI | | |
| NO. OF FEEDS | 40 | | |
| RANGE OF LONGITUDINAL FEEDS | 0.066 - 2 mm | | |
| RANGE OF TRANSVERSE FEEDS | 0.0165 - 0.5 mm | | |
| | | | |

| TAIL STOCK | |
|-----------------------------|--------|
| TAIL STOCK SPINDLE DIAMETER | 100 mm |
| TAPER IN TAIL STOCK QUILL | MT - 5 |

| TRAVEL AND TOOLS | |
|--------------------------|---------------------------|
| TRAVEL AND TOOLS | |
| CROSS SLIDE TRAVEL | 550 mm* |
| COMPOUND SLIDE TRAVEL | 250 mm |
| TAIL STOCK SLEEVE TRAVEL | 250 mm |
| TOOL POST SQUARE | 200 mm |
| TOOL SHANK SIZE | 38 mm |
| SUITABLE ELECTRICAL HP | 15 HP (3 phase) (960 RPM) |
| | |

STANDARD ACCESSORIES:

- CHUCK BACK PLATE
- CENTREADAPTER
- DEAD CENTRES 2 NOS
- TOOL POST SPANNER
- MOTOR PULLEY
- THREAD DIAL INDICATOR
- CHANGE GEAR SET
- CHIPTRAY
- NORTON GEAR BOX WITH DOUBLE SHAFT

OPTIONAL ACCESSORIES:

- INDEPENDENT CHUCK
- SELF CENTRING CHUCK
- CHUCK BACK PLATE EXTRA
- STEADY REST
- FOLLOW REST
- FACE PLATE
- CARRIER PLATE
- TAPER TURNING ATTACHMENT
- COOLANT PUMP WITH TANK AND FITTINGS
- ELECTRICALS (MOTOR, WIRING, SWITCH,
- V-BELTS AND FITTINGS)
- PANELBOARD
- SPLASH GUARD
- FOUNDATION ROUND PLATE WITH LEVELLING BOLTS
- QUICK CHANGE TOOL POST
- KEY WAY ATTACHMENT
- PADELSTOP
- ELECTRICAL THIRD SHAFT

NOTE: As improvements are constantly made in our machines, the above illustrations, specifications, dimensions and technical data are subject to modifications and change without prior notice and not binding on us.



Balaji Industrial Zone - A, Ribda Ardoi Road, Off National Highway, Ribda, Rajkot - 360 311. India. E-mail: vinit@balajilathe.com • Web: www.balajilathe.com • Cell: +91 94273 96228, 72260 41935.